



TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

RAYBO 26 — Slikit Scratch Resistance

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Scratch Resistance Additive (Air Dry)	Solvent	Can Be Used In Low Temperature Bake Systems	0.5-2% of Total Vehicle Solids	

PERFORMANCE

RAYBO 26 is intended for use in air dry systems as a scratch resistance additive. It can also be used in bake systems which will not be subjected to temperatures in excess of 200°F.

RAYBO 26 does not contribute to pinholing or intercoat adhesion loss.

RAYBO 26 becomes a part of the coating film and contributes to a low coefficient of friction for the coating surface.

ADVANTAGES

- Can be used in air dry and low bake systems
- Does not contribute to intercoat adhesion loss
- Fluid for ease of addition

RECOMMENDATIONS

For Scratch and Mar Resistance – 0.5-2% of Total Vehicle Solids
Can be added at any time including post addition. Use with lacquer systems or oxygenated solvents not recommended.

PHYSICAL DATA**

Weight/Gallon 6.7 lbs.
 Solids 40%
 Color Brown

CONTAINER SIZES

North American: 5 gal. pail*, 55 gal. drum, and bulk.
 Global Zones: 5 gal. pail*, 55 gal. drum.

* One gallon containers available upon request.

** Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

 Performance Additives
 Department
 Huntington, WV 25721
 Tel.: 304-525-5171
 Fax: 304-525-2921

U.S. Marketing Division
 Raybo Chemical Company
 Huntington, WV 25721
 Tel.: 304-525-5172
 Fax: 304-525-2921

 Exclusive Export
 Management Company
 W. R. Mangus, Inc.
 Tel.: 312-263-6124
 Email: rwmagnus@cocexport.com



Global Dist. Zones:
 Representatives in
 31 Countries