



TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

RAYBO 61 — AquaWet

Eliminates Fisheyes, Craters and Crawling

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Eliminates Fisheyes, Craters and Crawling	Water and Water Reducible	Can be Used for Dispersion	0.3-1% of Total Weight	

PERFORMANCE

RAYBO 61 effectively eliminates fisheyes, craters and crawling in water and water reducible systems. It also reduces water sensitivity during the first 24 to 36 hours of the coating cure period.

RAYBO 61 is active at the coating/substrate interface.

The superior wetting capabilities of RAYBO 61 also permit its use as a dispersant. When used for this purpose it is applicable to both organic and inorganic pigments. Its use can reduce mill time, eliminate puffy structures and control flocculation.

ADVANTAGES

- Superior wetting capability
- Reduces water sensitivity during cure
- Solids listed with USDA

RECOMMENDATIONS

For Surface Defects - 0.3-1% of Total Weight
Post addition is recommended
For Dispersion - 1-2% of Total Pigment Weight

PHYSICAL DATA**

Weight/Gallon 7.1 lbs.
Active Solids 60%
Appearance Amber Liquid

CONTAINER SIZES

North American: 5 gal. pail*, 55 gal. drum, and bulk.
Global Zones: 5 gal. pail*, 55 gal. drum.

* One gallon containers available upon request.

** Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

 Performance Additives
Department
Huntington, WV 25721
Tel.: 304-525-5171
Fax: 304-525-2921

U.S. Marketing Division
Raybo Chemical Company
Huntington, WV 25721
Tel.: 304-525-5172
Fax: 304-525-2921

 Exclusive Export
Management Company
W. R. Mangus, Inc.
Tel.: 312-263-6124
Email: rwmagnus@cocexport.com



Global Dist. Zones:
Representatives in
31 Countries