



TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

RAYBO 72 — VisCon

Viscosity and Sag Control

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Increases Viscosity and Sag Resistance	Solvent, Water Reducible	Non-thixotropic	1-3% of Vehicle Solids	

PERFORMANCE

RAYBO 72 is a viscosity and sag control additive for use in water reducible and solvent systems. This additive is not a puffing agent and does not introduce thixotropy to the system. When used for viscosity control the viscosity increase is proportional to the amount of additive used.

RAYBO 72 is especially useful for adjusting the occasional batch which may not meet specification for viscosity or sag resistance.

ADVANTAGES

- Can be post added
- Non-thixotropic

RECOMMENDATIONS

For Viscosity and Sag Control – 1-3% of Vehicle Solids
Post addition recommended. Overtreatment may retard drying time.
Not recommended for use with epoxy or urethane systems.

PHYSICAL DATA**

Weight/Gallon 7.15 lbs.
Gardner Viscosity E-F
Color Amber liquid

CONTAINER SIZES

North American: 5 gal. pail*, 55 gal. drum, and bulk.
Global Zones: 5 gal. pail*, 55 gal. drum.

* One gallon containers available upon request.

** Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

 Performance Additives
Department
Huntington, WV 25721
Tel.: 304-525-5171
Fax: 304-525-2921

U.S. Marketing Division
Raybo Chemical Company
Huntington, WV 25721
Tel.: 304-525-5172
Fax: 304-525-2921

 Exclusive Export
Management Company
W. R. Mangus, Inc.
Tel.: 312-263-6124
Email: rwmagnus@cocexport.com



Global Dist. Zones:
Representatives in
31 Countries