



Technical Data Sheet*

CSW 4050 USP Petrolatum

**Manufactured products shall conform to specifications. Revision Date: 8/14/2007*

| Test Description | Test Method | Min. | Max. | Typical |
|------------------------------|-------------|------------|----------|------------|
| MELT POINT °F(°C) | ASTM D-127 | 125 (51.7) | 140 (60) | 132 (55.6) |
| CONE PENETRATION, dmm @ 77°F | ASTM D-937 | 180 | 215 | 195 |
| LOVIBOND CELL, 2" CELL | | | | 0.8Y 0.1R |
| SAYBOLT COLOR | ASTM D-6045 | +10 | +20 | +16 |
| FIBER LENGTH | | | | Medium |

CSW 4050 is in compliance with the requirements established by the United States Pharmacopoeia and the U.S. FDA, 21 CFR 178.3700 for use in non-food articles in contact with food and 21 CFR 172.880 for use in food.

WARRANTY DISCLAIMER STATEMENT

Please be advised that there are no warranties, representations or conditions, expressed or implied, of any kind, including, but not limited to, merchantability or fitness for a particular purpose made by CLARUS SPECIALTY PRODUCTS, LLC (Hereafter "CLARUS") or its officers, employees or affiliates, in connection with the sale of the products described in this bulletin. The information contained in this document is based solely on tests, which are believed to be reliable. As actual conditions of use may vary and are beyond the control of CLARUS, the product's specified characteristics cannot be guaranteed and are offered solely for the buyer's evaluation and verification. Accordingly, the purchaser and each user assume all risks and liability connected to their specific use of such products. Nothing contained herein is to be construed as permission, recommendation or inducement by CLARUS or its officers, employees or affiliates, to use any product or process so as to infringe or conflict with any patent. Further, it is the user's obligation to utilize this material in full compliance with all required health, safety and environmental regulations. CLARUS recommends that the Material Safety Data Sheet for this product be consulted prior to handling and use.