



# TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

## RAYBO 218

### Corrosion Inhibitor for Ferrous Metals

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Organic and Inorganic Inhibitors Dissolved in Water	Water	Prevents Anionic Corrosion	1.0-3.0% of Total Weight	

#### PERFORMANCE

RAYBO 218 is a blend of organic and inorganic corrosion inhibitors formulated to protect ferrous parts when applied from water based organic cleaners or coatings. Effectively retards anionic corrosion and prevents flash rust.

#### ADVANTAGES

- No amine odor
- Can be applied from film forming and non film forming systems
- Effective against flash rust and filiform corrosion during storage
- Not formulated to enhance salt fog protection

#### RECOMMENDATIONS

1.0-3.0% based on total weight

#### PHYSICAL DATA\*\*

Weight/Gallon . . . . . 9.0 lbs.  
 Viscosity . . . . . 14 sec. #2 Zahn cup  
 pH . . . . . 10.3

#### CONTAINER SIZES

North American: 5 gal. pail\*, 55 gal. drum, and bulk.  
 Global Zones: 5 gal. pail\*, 55 gal. drum.

\* One gallon containers available upon request.

\*\* Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

 Performance Additives  
 Department  
 Huntington, WV 25721  
 Tel.: 304-525-5171  
 Fax: 304-525-2921

U.S. Marketing Division  
 Raybo Chemical Company  
 Huntington, WV 25721  
 Tel.: 304-525-5172  
 Fax: 304-525-2921

 Exclusive Export  
 Management Company  
 W. R. Mangus, Inc.  
 Tel.: 312-263-6124  
 Email: rwmagnus@cocexport.com



Global Dist. Zones:  
 Representatives in  
 31 Countries